Avaya Aura® Experience Portal 6.0 Voluntary Product Accessibility Template (VPAT)

Avaya Aura Experience Portal 6.0 is a software platform that enables organizations to implement and deliver multi-modal inbound and outbound self-service applications. The statements in this document refer to the telephone user interfaces that may be implemented on the Experience Portal platform.

The purpose of the typical Experience Portal application is to provide telephone users with a voice-based natural-language interface to Web applications. Despite having been designed as a voice input/output product, Experience Portal is able to accept DTMF ("touch tone") responses and is also able to provide Baudot-format prompts for TTY users.

§ 1194.23 Telecommunications Products

Criteria	Support Levels	Remarks and Explanations
1194.23(a) Telecommunications products or systems which provide a function allowing voice communication and which do not themselves provide a TTY functionality shall provide a standard	Supports	All end-user communication with Avaya Aura Experience Portal 6.0 is via standard telephone lines, thereby satisfying the requirement for a non- acoustic connection point for TTYs.
non-acoustic connection point for TTYs. Microphones shall be capable of being turned on and off to allow the user to intermix speech with TTY use.		With regard to intermixing speech and TTY use, many vendors have stated that this requirement applies only to telephones, and does not apply to products such as the Experience Portal. By contrast, Avaya believes that the ability to intermix speech and TTY is essential. Here's why: nearly half of the people who use TTYs do so in a mixed-mode fashion, the most common being people who are hard of hearing but are still able to speak clearly. These individuals often prefer to receive on their TTYs and then speak in response, a process referred to as Voice Carry Over or VCO. For this reason, Avaya Aura Experience Portal 6.0 supports the execution of VoiceXML applications that allow end-users to respond by voice even when being prompted by TTY text.
1194.23(b) Telecommunications products, which include voice communication functionality, shall support all commonly used crossmanufacturer non-proprietary standard TTY signal protocols.	Supports	The only TTY protocol that the US Access Board presently requires is TIA/EIA 825, commonly referred to as 45.45 baud Baudot signaling. Support for protocols such as 300 baud ASCII and 1200 baud ASCII is not feasible with IVR systems because these

are communicating with each other, thereby making it impossible to intermix voice and DTMF signals ("touch tones") with the TTY transmissions. Please note the following guidance: (1) Avaya Aura Experience Portal 6.0 can be configured to use any of the voice encoding alignifimes supported by the voice encoding alignifimes supported by the voice encoding alignifimes supported by the VoiceXML 2.0/2.1 standard. To ensure reliable recording and playback of Baudot TTY signals, a 64 kilobit/second pulse code modulation technique, such as ITU-T Recommendation G.711, must be used. (2) Avaya Aura Experience Portal 6.0 supports SIP and H.323 telephony integration. If packet loss on the IP network between the Experience Portal and the end-user exceeds 0.12%, the TTY character error rate may exceed the FCC's suggested limit of one percent. Note that, because WANs yipically do not support a packet loss rate of less than 0.12%, IP QSIG funks are recommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are tree systems are terminate on remote systems are teresommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are voice or TTY, users may respond by voice or via DTMF 'touch tone' key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.) NOTE: In most cases, the applications that operate on Avaya Aura Experience			protocols require a constant carrier tone to be maintained between devices that
(1) Avaya Aura Experience Portal 6.0 can be configured to use any of the voice encoding algorithms supported by the Voice XML 2.0/2.1 standard. To ensure reliable recording and playback of Baudot TTY signals, a 64 kilobit/second pulse code modulation technique, such as ITU-T Recommendation G.711, must be used. (2) Avaya Aura Experience Portal 6.0 supports SIP and H.323 telephony integration. If packet loss on the IP network between the Experience Portal and the end-user exceeds 0.12%, the TTY character the Experience Portal and the end-user exceeds 0.12% the TTY character for rate may exceed the FCC's suggested limit of one percent. Note that, because WANs typically do not support a packet loss rate of less than 0.12%, IP QSIG trunks are recommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are transported reliably. It is the purchaser's responsibility to ensure that the Experience Portal is used in conjunction with a robust IP network. 1194.23(c) Voice mail, auto-attended to the construction of the provide voice prompts, avaya Aura Experience Portal is used in conjunction with a robust IP network. In addition to its ability to provide voice prompts, Avaya Aura Experience Portal's 6.0 is able to provide 45.45 baud and 50 baud Baudorformat prompts to TTY users. Regardless of whether the prompts are voice or TTY, users may respond by voice or via to TTM "fouch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.) NOTE: In most cases, the applications that operate on Avaya Aura Experience			are communicating with each other, thereby making it impossible to intermix voice and DTMF signals ("touch tones")
can be configured to use any of the voice encoding algorithms supported by the VoiceXML 2.0/2.1 standard. To ensure reliable recording and playback of Baudot TTY signals, a 64 kilobit/second pulse code modulation technique, such as ITU-T Recommendation G.711, must be used. (2) Avaya Aura Experience Portal 6.0 supports SIP and H.323 telephony integration. If packet loss on the IP network between the Experience Portal and the end-use receeds 0.12%, the TTY character error rate may exceed the FCC's suggested limit of one percent. Note that, because WANs typically do not support a packet loss rate of less than 0.12%, IP QSIG trunks are recommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are transported reliably. It is the purchaser's responsibility to ensure that the Experience Portal is used in conjunction with a robust IP network. In addition to its ability to provide voice attendant, and interactive voice responsibility to ensure that the Experience Portal subset of the prompts are voice or TTY, users may respond by voice or via DTMF "touch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompts or TTY users. Regardless of whether the prompts are voice or TTY, users may respond by voice or via DTMF "touch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.) NOTE: In most cases, the applications that operate on Avaya Aura Experience			Please note the following guidance:
supports SIP and H.323 telephony integration. If packet loss on the IP network between the Experience Portal and the end-user exceeds 0.12%, the TTY character error rate may exceed the FCC's suggested limit of one percent. Note that, because WANs typically do not support a packet loss rate of less than 0.12%, IP QSIG trunks are recommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are transported reliably. It is the purchaser's responsibility to ensure that the Experience Portal is used in conjunction with a robust IP network. 1194.23(c) Voice mail, auto-attendant, and interactive voice response telecommunications systems shall be usable by TTY users with their TTYs. Supports In addition to its ability to provide voice prompts, Avaya Aura Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.) NOTE: In most cases, the applications that operate on Avaya Aura Experience			can be configured to use any of the voice encoding algorithms supported by the VoiceXML 2.0/2.1 standard. To ensure reliable recording and playback of Baudot TTY signals, a 64 kilobit/second pulse code modulation technique, such as ITU-T
attendant, and interactive voice response telecommunications systems shall be usable by TTY users with their TTYs. prompts, Avaya Aura Experience Portal 6.0 is able to provide 45.45 baud and 50 baud Baudot-format prompts to TTY users. Regardless of whether the prompts are voice or TTY, users may respond by voice or via DTMF "touch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.) NOTE: In most cases, the applications that operate on Avaya Aura Experience			supports SIP and H.323 telephony integration. If packet loss on the IP network between the Experience Portal and the end-user exceeds 0.12%, the TTY character error rate may exceed the FCC's suggested limit of one percent. Note that, because WANs typically do not support a packet loss rate of less than 0.12%, IP QSIG trunks are recommended for the connections between Avaya Communication Manager systems, in order to ensure that TTY signals that terminate on remote systems are transported reliably. It is the purchaser's responsibility to ensure that the Experience Portal is used in conjunction
that operate on Avaya Aura Experience	attendant, and interactive voice response telecommunications systems shall be usable by TTY	Supports	In addition to its ability to provide voice prompts, Avaya Aura Experience Portal 6.0 is able to provide 45.45 baud and 50 baud Baudot-format prompts to TTY users. Regardless of whether the prompts are voice or TTY, users may respond by voice or via DTMF "touch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.)

		owners and managers of the systems, rather than by Avaya. For this reason, even though Avaya provides tools that allow fully conformant applications to be implemented, it will often be the purchaser's responsibility to ensure conformance with this requirement.
1194.23(d) Voice mail, messaging, auto-attendant, and interactive voice response telecommunications systems that require a response	Supports	Avaya Aura Experience Portal 6.0 supports the creation of applications that do not require a response within a time interval.
from a user within a time interval, shall give an alert when the time interval is about to run out, and shall provide sufficient time for the user to indicate more time is required.		A reason why IVR applications often require a response within a time interval is that, if the application does not disconnect or take other action automatically after a period of user inactivity, it becomes possible for callers to freeze the ports on the system indefinitely.
		Avaya Aura Experience Portal 6.0 permits time limits to be handled in a flexible, user-friendly manner. Within applications that impose a time limit on users' responses, the time-out interval may be specified within the application, along with the behavior of the system when time is about to expire. System responses that may be specified in the applications include, but are not limited to, providing an alert when the time interval is about to run out and providing sufficient time for the user to indicate more time is required, repeating the menu, and transferring the call automatically to a person who can assist the caller.
		NOTE: In most cases, the applications that operate on Avaya Aura Experience Portal platforms are implemented by the owners and managers of the systems, rather than by Avaya. For this reason, even though Avaya provides tools that allow fully conformant applications to be implemented, it will often be the purchaser's responsibility to ensure conformance with this requirement.
1194.23(e) Where provided, caller identification and similar telecommunications functions shall also be available for users of TTYs,	Not Applicable	This requirement applies to endpoint devices that are co-located with the user, such as telephones, soft phones, and TTYs. It does not apply to Avaya
and for users who cannot see displays. Avaya Aura Experience Portal 6.0		Aura Experience Portal 6.0. There is no aspect of Avaya Aura Page 3 of 9

		Experience Portal 6.0 that would
		interfere with the operation of a conforming endpoint device.
1194.23(f) For transmitted voice	Supports with Exceptions	Avaya Aura Experience Portal 6.0
signals, telecommunications	Supports with Exceptions	conforms to this requirement, within the
products shall provide a gain		limitations of the VoiceXML 2.0/2.1
adjustable up to a minimum of 20		standard and to the extent feasible with
dB. For incremental volume control,		equipment that is not co-located with
at least one intermediate step of 12		the user.
dB of gain shall be provided.		The street of the line A second
		The voice prompts provided by Avaya Aura Experience Portal 6.0 can consist
		of pre-recorded speech or can be
		generated by text-to-speech software.
		, ,
		The VoiceXML 2.0/2.1 standard utilized by Experience Portal does not support
		audio gain adjustments of pre-recorded
		speech. Conformance with this
		requirement can be achieved by
		creating and storing multiple versions of
		each speech recording, encoded at
		different amplitude levels. Alternatively,
		the amplitude of text-to-speech audio output can be modified in the Speech
		Synthesis Markup Language (SSML).
		The available user-adjustable amplitude
		range (i.e., the lowest user-selectable
		amplitude versus the highest user-
		selectable amplitude) is determined by
		the third party speech technology that is
		used.
		NOTE: None of the commonly accepted
		standards for voice communication
		between telephones and associated
		back-office equipment (such as IVR systems) has 20 dB of amplitude
		headroom available. Under typical
		conditions, the maximum additional gain
		in the output of back-office systems,
		without introducing unacceptable levels
		of distortion, is approximately 10 dB.
		For this reason, users who require low-
		distortion amplitude increases of more than 10 dB above the nominal level
		should rely on their endpoint devices
		(e.g., their telephones), rather than the
		Experience Portal, to provide this gain.
		All Avaya desktop telephones may be
		equipped with user-adjustable variable
		amplified handsets that satisfy this
1194.23(g) If the telecommunications	Supports	requirement. All user-adjustable audio characteristics
product allows a user to adjust the	Сарроно	on Avaya Aura Experience Portal 6.0
LIFT TABLE AND IN CARGO TO ANGUST 1110	I	

receive volume, a function shall be		evetome euch as playback amplituda
provided to automatically reset the volume to the default level after every use.		systems, such as playback amplitude, playback rate, and call-answer prompting language, can be programmed in the application layer to reset automatically to their default
		values when the user hangs up.
1194.23(h) Where a telecommunications product delivers output by an audio transducer which is normally held up to the ear, a means for effective magnetic wireless coupling to hearing technologies shall be provided.	Not Applicable	This requirement applies to transducer- equipped endpoint devices, such as telephone handsets and headsets. It does not apply to Avaya Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.
1194.23(i) Interference to hearing technologies (including hearing aids, cochlear implants, and assistive listening devices) shall be reduced to the lowest possible level that allows a user of hearing technologies to utilize the telecommunications product.	Not Applicable	This requirement applies to transducer- equipped endpoint devices, such as telephone handsets and headsets. It does not apply to Avaya Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.
1194.23(j) Products that transmit or conduct information or communication, shall pass through cross-manufacturer, non-proprietary, industry-standard codes, translation protocols, formats or other information necessary to provide the information or communication in a usable format. Technologies which use encoding, signal compression, format transformation, or similar techniques shall not remove information needed for access or shall restore it upon delivery.	Supports	The manner in which Avaya Aura Experience Portal 6.0 conforms to this requirement is described in the response to 1194.23(b).
1194.23(k)(1) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be tactilely discernible without activating the controls or keys.	Not Applicable	This requirement applies to endpoint devices that are co-located with the user, such as telephones, soft phones, and TTYs. It does not apply to Avaya Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.
1194.23(k)(2) Products which have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be operable	Not Applicable	This requirement applies to endpoint devices that are co-located with the user, such as telephones, soft phones, and TTYs. It does not apply to Avaya

with one hand and shall not require tight grasping, pinching, twisting of the wrist. The force required to activate controls and keys shall be 5 lbs. (22.2N) maximum.		Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.
1194.23(k)(3) Products which have mechanically operated controls or keys shall comply with the following: If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character.	Not Applicable	This requirement applies to endpoint devices that are co-located with the user, such as telephones, soft phones, and TTYs. It does not apply to Avaya Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.
1194.23(k)(4) Products which have mechanically operated controls or keys shall comply with the following: The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound.	Not Applicable	This requirement applies to endpoint devices that are co-located with the user, such as telephones, soft phones, and TTYs. It does not apply to Avaya Aura Experience Portal 6.0. There is no aspect of Avaya Aura Experience Portal 6.0 that would interfere with the operation of a conforming endpoint device.

§ 1194.31 Functional Performance Criteria

Ouitouio	Commont Lovele	Demonto and Explanations
Criteria	Support Levels	Remarks and Explanations
1194.31(a) At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for assistive technology used by people who are blind or visually impaired shall be provided.	Supports.	Avaya Aura Experience Portal 6.0 supports a telephone user interface that is operable without user vision. NOTE: In most cases, the applications that operate on Avaya Aura Experience Portal platforms are implemented by the owners and managers of the systems, rather than by Avaya. For this reason, even though Avaya provides tools that allow fully conformant applications to be implemented, it will often be the purchaser's responsibility to ensure
1194.31(b) At least one mode of	Supports.	conformance with this requirement. Avaya Aura Experience Portal 6.0
operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided	Сарропо.	supports a telephone user interface that is operable without user vision.
in audio and enlarged print output		NOTE: In most cases, the applications
working together or independently,		that operate on Avaya Aura Experience
or support for assistive technology		Portal platforms are implemented by the
used by people who are visually		owners and managers of the systems,

impaired shall be provided.		rather than by Avaya. For this reason,
		even though Avaya provides tools that allow fully conformant applications to be implemented, it will often be the purchaser's responsibility to ensure conformance with this requirement.
1194.31(c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for assistive technology used by people who are deaf or hard of hearing shall be provided.	Supports.	In addition to its ability to provide voice prompts, Avaya Aura Experience Portal 6.0 is able to provide 45.45 baud and 50 baud Baudot-format prompts to TTY users. Regardless of whether the prompts are voice or TTY, users may respond by voice or via DTMF "touch tone" key presses. (Experience Portal's ability to accept spoken responses, even when prompting in TTY format, can be very helpful to Voice Carry Over or "VCO" users who are unable to hear adequately on a telephone but are nevertheless able to speak clearly.)
		NOTE: In most cases, the applications that operate on Avaya Aura Experience Portal platforms are implemented by the owners and managers of the systems, rather than by Avaya. For this reason, even though Avaya provides tools that allow fully conformant applications to be implemented, it will often be the purchaser's responsibility to ensure conformance with this requirement.
1194.31(d) Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided.	Supports with Exceptions	Avaya Aura Experience Portal 6.0 conforms to this requirement, within the limitations of the VoiceXML 2.0/2.1 standard and to the extent feasible with equipment that is not co-located with the user. The voice prompts provided by Avaya Aura Experience Portal 6.0 can consist of pre-recorded speech or can be generated by text-to-speech software.
		The VoiceXML 2.0/2.1 standard utilized by Experience Portal does not support audio gain adjustments or playback rate adjustments of pre-recorded speech. Conformance with this requirement can be achieved by creating and storing multiple versions of each speech recording, encoded at different amplitude levels or different playback rates. Alternatively, the amplitude and playback rate of text-to-speech audio output can be modified in the Speech

		Synthesis Markup Language (SSML). The available user-adjustable amplitude range (i.e., the lowest user-selectable amplitude versus the highest user-selectable amplitude) and playback rate (extra slow through extra fast) is determined by the third party speech technology that is used.
		NOTE: None of the commonly accepted standards for voice communication between telephones and associated back-office equipment (such as IVR systems) has 20 dB of amplitude headroom available. Under typical conditions, the maximum additional gain in the output of back-office systems, without introducing unacceptable levels of distortion, is approximately 10 dB. For this reason, users who require low-distortion amplitude increases of more than 10 dB above the nominal level should rely on their endpoint devices (e.g., their telephones), rather than the Experience Portal, to provide this gain.
1194.31(e) At least one mode of operation and information retrieval	Supports.	In most cases, the applications that operate on Avaya Aura Experience
that does not require user speech		Portal platforms are implemented by the
shall be provided, or support for		owners and managers of the systems,
assistive technology used by people		rather than by Avaya. For this reason,
with disabilities shall be provided.		even though Avaya provides tools that allow fully conformant applications to be
		implemented, it will often be the
		purchaser's responsibility to ensure
		conformance with this requirement.
		(Typically, this is achieved by allowing DTMF "touch tone" key presses
		whenever user input is required.)
1194.31(f) At least one mode of	Supports.	Avaya Aura Experience Portal 6.0
operation and information retrieval		supports the creation of applications
that does not require fine motor control or simultaneous actions and		that do not require fine motor control skills or simultaneous actions.
that is operable with limited reach		c.i.iio oi oiiiid.iio do dolloiio.
and strength shall be provided.		Applications that operate on Avaya
		Aura Experience Portal can be developed to support single DTMF
		entries as well as natural language
		speech input.
		NOTE: In most cases, the applications that operate on Avaya Aura Experience
		Portal platforms are implemented by the
		owners and managers of the systems, rather than by Avaya. For this reason,
		even though Avaya provides tools that
Avava Aura Experience Portal 6.0		Page 8 of 9

allow fully conformant applications to be
implemented, it will often be the
purchaser's responsibility to ensure
conformance with this requirement.

§ 1194.41 Information, Documentation and Support

Criteria	Support Levels	Remarks and Explanations
1194.41(a) Product support documentation provided to endusers shall be made available in alternate formats upon request, at no additional charge	Supports.	Will provide upon request.
1194.41(b) End-users shall have access to a description of the accessibility and compatibility features of products in alternate formats or alternate methods upon request, at no additional charge.	Supports	Will provide upon request.
1194.41(c) Support services for products shall accommodate the communication needs of end-users with disabilities.	Supports	Avaya's point-of-contact for accessibility-related issues: Dr. Paul R. Michaelis Voice: 303-538-4101 TTY: 303-538-3740 prmichaelis-at-avaya.com

© 2011 Avaya Inc.

All rights reserved. Except as specifically stated, none of the material may be copied, reproduced, distributed, republished, downloaded, displayed, posted, or transmitted in any form without authorized, prior written permission from Avaya Inc. Permission is granted for you to make a single copy of Avaya Inc. "Section 508" documents, solely for informational and non-commercial use within your organization, provided that you keep intact all copyright and other proprietary notices. No other use of the information provided is authorized.

This market information is provided, pursuant to FAR Part 39.2, to be used by Requiring Officers. It is not intended to represent a certification for compliance. Any statement of compliance or conformance indicated on this document is an indication that the product shall be capable, at the time of its delivery, when used in accordance with Avaya's associated documents, and other written information provided to the government, of providing comparable access to individuals with disabilities consistent with the designated provision of the Standards, provided that any assistive technologies used with the product properly interoperates with it and other assistive technologies.

Updated 14 August 2011